

Load and Inflation Table for Radial Truck-Bus Tires

TIRE SIZE DESIGNATION	USAGE	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES													
		kPa	480	520	550	590	620	660	690	720	760	790	830	860	900
		psi	70	75	80	85	90	95	100	105	110	115	120	125	130
215/75R17.5	DUAL	kg	1300	1390	1450	1540	1600	1680	1740	1800	1880	1940	2020	2060(H)	
		lbs.	2865	3065	3195	3395	3525	3705	3835	3970	4145	4275	4455	4540(H)	
	SINGLE	kg	1380	1470	1540	1630	1690	1780	1850	1910	1990	2060	2140	2180(H)	
		lbs.	3040	3240	3395	3595	3725	3925	4080	4210	4385	4540	4720	4805(H)	
245/70R17.5	DUAL	kg	1590	1700	1780	1880	1950	2050	2130	2200	2300	2370	2470	2575(U)	
		lbs.	3505	3750	3925	4145	4300	4520	4695	4850	5070	5225	5445	5675(U)	
	SINGLE	kg	1690	1800	1880	1990	2070	2170	2250	2330	2430	2510	2610	2725(U)	
		lbs.	3725	3970	4145	4385	4565	4785	4960	5135	5355	5535	5755	6005(U)	
225/70R19.5	DUAL	kg	1230	1300	1360	1410	1470	1550	1580	1640	1700(G)				
		lbs.	2720	2860	3000	3115	3245	3415	3490	3615	3750(G)				
	SINGLE	kg	1310	1380	1450	1500	1570	1650	1690	1740	1800(G)				
		lbs.	2895	3040	3195	3315	3450	3640	3715	3845	3970(G)				
245/70R19.5	DUAL	kg	1390	1460	1550	1590	1660	1750	1790	1850	1950	2040	2120(H)		
		lbs.	3070	3220	3415	3515	3655	3860	3940	4075	4300	4520	4675(H)		
	SINGLE	kg	1480	1550	1650	1700	1770	1850	1900	1970	2060	2150	2240(H)		
		lbs.	3265	3425	3640	3740	3890	4080	4190	4335	4540	4740	4940(H)		
11R22.5	DUAL	kg	1990	2080	2160	2250	2360	2460	2560	2650(G)	2680	2710	2725(H)		
		lbs.	4380	4580	4760	4950	5205	5415	5625	5840(G)	5895	5950	6005(H)		
	SINGLE	kg	2050	2160	2260	2370	2500	2600	2700	2800(G)	2870	2940	3000(H)		
		lbs.	4530	4770	4990	5220	5510	5730	5950	6175(G)	6320	6465	6610(H)		
255/70R22.5	DUAL	kg	1630	1710	1800	1860	1940	2000	2020	2090	2120	2230	2300(H)		
		lbs.	3585	3765	3970	4110	4275	4410	4455	4610	4675	4915	5070(H)		
	SINGLE	kg	1730	1820	1900	1980	2060	2120	2220	2300	2360	2450	2500(H)		
		lbs.	3815	4005	4190	4370	4550	4675	4895	5065	5205	5400	5510(H)		
275/70R22.5	DUAL	kg	1750	1870	1960	2070	2150	2260	2340	2430	2530	2610	2720	2800	2900(J)
		lbs.	3860	4125	4320	4565	4740	4980	5160	5355	5580	5755	5995	6175	6395(J)
	SINGLE	kg	1910	2030	2120	2250	2340	2460	2550	2640	2750	2840	2950	3040	3150(J)
		lbs.	4210	4475	4675	4960	5160	5425	5620	5820	6065	6260	6505	6700	6940(J)
295/75R22.5	DUAL	kg	1860	1950	2060	2130	2220	2300	2390	2470	2575(G)	2680	2820	3000(H)	
		lbs.	4095	4300	4540	4690	4885	5070	5260	5440	5675(G)	5920	6220	6610(H)	
	SINGLE	kg	2040	2140	2240	2340	2440	2500	2620	2710	2800(G)	2950	3100	3250(H)	
		lbs.	4500	4725	4940	5155	5370	5510	5780	5980	6175(G)	6500	6830	7160(H)	
315/80R22.5	DUAL	kg	2680	2810	3000	3070	3190	3350	3440	3560	3650	3790	3875	4010	4125(L)
		lbs.	5900	6190	6610	6760	7030	7390	7570	7840	8050	8350	8540	8850	9090(L)
	SINGLE	kg	2940	3090	3250	3370	3510	3650	3780	3910	4000	4160	4250	4410	4540(L)
		lbs.	6485	6800	7160	7430	7730	8050	8320	8610	8820	9180	9370	9730	10000(L)
385/65R22.5	SINGLE	kg	2880	3060	3150	3350	3470	3650	3740	3850	4000	4100	4250	4380	4500(L)
		lbs.	6380	6720	6940	7350	7650	8050	8230	8510	8820	9050	9370	9650	9920(L)
425/65R22.5	SINGLE	kg	3430	3640	3750	3980	4130	4250	4440	4580	4750	4880	5150(L)		
		lbs.	7590	7990	8270	8740	9100	9370	9790	10100	10500	10700	11400(L)		
11R24.5	DUAL	kg	2110	2210	2300	2390	2500	2580	2660	2725(G)	2820	2910	3000(H)		
		lbs.	4660	4870	5070	5260	5510	5675	5840	6005(G)	6205	6405	6610(H)		
	SINGLE	kg	2190	2300	2410	2520	2650	2770	2890	3000(G)	3080	3160	3250(H)		
		lbs.	4820	5070	5310	5550	5840	6095	6350	6610(G)	6790	6970	7160(H)		
285/75R24.5	DUAL	kg	1870	1970	2060	2150	2240	2360	2410	2490	2575(G)	2660	2800(H)		
		lbs.	4135	4340	4540	4740	4930	5205	5310	5495	5675(G)	5860	6175(H)		
	SINGLE	kg	2060	2160	2240	2360	2460	2575	2650	2740	2800(G)	2920	3075(H)		
		lbs.	4545	4770	4940	5210	5450	5675	5835	6040	6175(G)	6440	6780(H)		