

2019 RAM 2500 Box Delete/IVD Trailer Towing Chart - SAE J2807 Compliant.

Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		VECI Label		UVW	Max Upfit Weight	GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear	MCVW	Frontal Area (ft ²)				
RAM 2500 4X2 REG TRADESMAN With Box Delete Option [XBC]															
6.4L V8 Hemi with MDS	8HP75 8 Speed	3.73	10,000	4,520	5,477	3,447	2,031	5,500	6,390	8,500	58	8,000	2,523	21,500	14,900
6.4L V8 Hemi with MDS	8HP75 8 Speed	4.10	10,000	4,520	5,477	3,447	2,031	5,500	6,390	8,500	58	8,000	2,523	24,000	17,400
RAM 2500 4X2 REG TRADESMAN With Box Delete Option [XBC] CANADA ONLY															
6.4L V8 Hemi with MDS	8HP75 8 Speed	3.73	9,900	4,420	5,477	3,447	2,031	5,500	6,390	8,500	58	8,000	2,523	21,500	14,900
6.4L V8 Hemi with MDS	8HP75 8 Speed	4.10	9,900	4,420	5,477	3,447	2,031	5,500	6,390	8,500	58	8,000	2,523	24,000	17,400
RAM 2500 4X2 CREW TRADESMAN With Box Delete Option [XBC]															
6.4L V8 Hemi with MDS	8HP75 8 Speed	3.73	10,000	4,040	5,964	3,653	2,311	5,500	6,390	8,500	58	8,000	2,036	21,500	14,500
6.4L V8 Hemi with MDS	8HP75 8 Speed	4.10	10,000	4,040	5,964	3,653	2,311	5,500	6,390	8,500	58	8,000	2,036	24,000	17,000
RAM 2500 4X2 CREW TRADESMAN With Box Delete Option [XBC] CANADA ONLY															
6.4L V8 Hemi with MDS	8HP75 8 Speed	3.73	9,900	3,940	5,964	3,653	2,311	5,500	6,390	8,500	58	8,000	2,036	21,500	14,500
6.4L V8 Hemi with MDS	8HP75 8 Speed	4.10	9,900	3,940	5,964	3,653	2,311	5,500	6,390	8,500	58	8,000	2,036	24,000	17,000
RAM 2500 4X2 CREW TRADESMAN With Box Delete Option [XBC]															
6.4L V8 Hemi with MDS	8HP75 8 Speed	3.73	10,000	4,030	5,966	3,712	2,254	5,500	6,390	8,500	58	8,000	2,034	21,500	14,420
6.4L V8 Hemi with MDS	8HP75 8 Speed	4.10	10,000	4,030	5,966	3,712	2,254	5,500	6,390	8,500	58	8,000	2,034	24,000	16,920
RAM 2500 4X2 CREW TRADESMAN With Box Delete Option [XBC] CANADA ONLY															
6.4L V8 Hemi with MDS	8HP75 8 Speed	3.73	9,900	3,930	5,966	3,712	2,254	5,500	6,390	8,500	58	8,000	2,034	21,500	14,420
6.4L V8 Hemi with MDS	8HP75 8 Speed	4.10	9,900	3,930	5,966	3,712	2,254	5,500	6,390	8,500	58	8,000	2,034	24,000	16,920
RAM 2500 4X4 REG TRADESMAN With Box Delete Option [XBC]															
6.4L V8 Hemi with MDS	8HP75 8 Speed	3.73	10,000	4,170	5,829	3,747	2,082	5,500	6,390	8,500	58	8,000	2,171	21,500	14,550
6.4L V8 Hemi with MDS	8HP75 8 Speed	4.10	10,000	4,170	5,829	3,747	2,082	5,500	6,390	8,500	58	8,000	2,171	24,000	17,050
RAM 2500 4X4 REG TRADESMAN With Box Delete Option [XBC] CANADA ONLY															
6.4L V8 Hemi with MDS	8HP75 8 Speed	3.73	9,900	4,070	5,826	3,673	2,153	5,500	6,390	8,500	58	8,000	2,174	21,500	14,550
6.4L V8 Hemi with MDS	8HP75 8 Speed	4.10	9,900	4,070	5,826	3,673	2,153	5,500	6,390	8,500	58	8,000	2,174	24,000	17,050
RAM 2500 4X4 CREW TRADESMAN With Box Delete Option [XBC]															
6.4L V8 Hemi with MDS	8HP75 8 Speed	3.73	10,000	3,730	6,269	3,948	2,321	5,500	6,390	8,500	58	8,000	1,731	21,500	14,190
6.4L V8 Hemi with MDS	8HP75 8 Speed	4.10	10,000	3,730	6,269	3,948	2,321	5,500	6,390	8,500	58	8,000	1,731	24,000	16,690
RAM 2500 4X4 CREW TRADESMAN With Box Delete Option [XBC] CANADA ONLY															
6.4L V8 Hemi with MDS	8HP75 8 Speed	3.73	9,900	3,630	6,269	3,948	2,321	5,500	6,390	8,500	58	8,000	1,731	21,500	14,190
6.4L V8 Hemi with MDS	8HP75 8 Speed	4.10	9,900	3,630	6,269	3,948	2,321	5,500	6,390	8,500	58	8,000	1,731	24,000	16,690
RAM 2500 4X4 CREW TRADESMAN With Box Delete Option [XBC]															
6.4L V8 Hemi with MDS	8HP75 8 Speed	3.73	10,000	3,640	6,356	4,012	2,344	5,500	6,390	8,500	58	8,000	1,644	21,500	14,030
6.4L V8 Hemi with MDS	8HP75 8 Speed	4.10	10,000	3,640	6,356	4,012	2,344	5,500	6,390	8,500	58	8,000	1,644	24,000	16,530
RAM 2500 4X4 CREW TRADESMAN With Box Delete Option [XBC] CANADA ONLY															
6.4L V8 Hemi with MDS	8HP75 8 Speed	3.73	9,900	3,530	6,373	3,981	2,392	5,500	6,390	8,500	58	8,000	1,627	21,500	14,020
6.4L V8 Hemi with MDS	8HP75 8 Speed	4.10	9,900	3,530	6,373	3,981	2,392	5,500	6,390	8,500	58	8,000	1,627	24,000	16,510

NOTES:

Payload and Max Trailer Weights are ESTIMATED values

All values are shown in pounds unless otherwise stated

Payload and Max Trailer Weight values are rounded to the nearest 10 lbs

Payload = GVWR - Base Weight

GAWRs, GVWRs, and GCWRs should never be exceeded

Recommended tongue weight determined by class hitch receiver and hardware limits of upfit


Upfit or Aftermarket equipment weight not included in Base Weight

MCVW: Maximum Completed Vehicle Weight, includes Total Base Weight + permanently attached Upfit Weight

Frontal Area: Maximum allowable Frontal Area, in Ft², that the vehicle can project. For details on calculations please refer to Ram Body Builders Guide.

VECI Label & Max Upfit Weight n/a: Vehicle is not restricted to MCVW, Frontal Area, or Maximum Upfit Weight limits, however GVWR/GAWR/GCWR cannot be exceeded.

UVW: Unloaded Vehicle Weight specified per FMVSS 301: Fuel System Integrity, applicable to vehicles <10k lbs GVW only

 Indicates Max Payload/Upfit Weight/Trailer Weight

2019 RAM 3500 Box Delete/IVD Trailer Towing Chart - SAE J2807 Compliant

Engine	Transmission	Single / Dual Rear Wheel	Axle Ratio	GVWR	Payload	Base Weight			GAWR		VECI Label		Max Upfit Weight	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear	MCVW	Frontal Area (ft ²)		
RAM 3500 4X2 REG CAB TRADESMAN Box Delete Option [XBC]														
6.4L V8 Hemi with MDS	8HP75 8 Speed	SRW	3.73	10,700	5,190	5,506	3,441	2,065	5,500	7,000	8,500	58	2,994	14,870
6.4L V8 Hemi with MDS	8HP75 8 Speed	SRW	4.10	10,700	5,190	5,506	3,441	2,065	5,500	7,000	8,500	58	2,994	17,370
RAM 3500 4X2 CREWCAB TRADESMAN Box Delete Option [XBC]														
6.4L V8 Hemi with MDS	8HP75 8 Speed	SRW	3.73	10,700	4,720	5,984	3,670	2,314	5,500	7,000	8,500	58	2,516	14,480
6.4L V8 Hemi with MDS	8HP75 8 Speed	SRW	4.10	10,700	4,720	5,984	3,670	2,314	5,500	7,000	8,500	58	2,516	16,980
RAM 3500 4X2 CREWCAB TRADESMAN Box Delete Option [XBC]														
6.4L V8 Hemi with MDS	8HP75 8 Speed	SRW	3.73	11,100	5,080	6,019	3,749	2,270	5,500	7,000	8,500	58	2,481	14,370
6.4L V8 Hemi with MDS	8HP75 8 Speed	SRW	4.10	11,100	5,080	6,019	3,749	2,270	5,500	7,000	8,500	58	2,481	16,870
RAM 3500 4X4 REG CAB TRADESMAN Box Delete Option [XBC]														
6.4L V8 Hemi with MDS	8HP75 8 Speed	SRW	3.73	11,000	5,130	5,869	3,742	2,127	5,500	7,000	8,500	58	2,631	14,510
6.4L V8 Hemi with MDS	8HP75 8 Speed	SRW	4.10	11,000	5,130	5,869	3,742	2,127	5,500	7,000	8,500	58	2,631	17,010
RAM 3500 4X4 CREWCAB TRADESMAN Box Delete Option [XBC]														
6.4L V8 Hemi with MDS	8HP75 8 Speed	SRW	3.73	11,000	4,720	6,278	3,927	2,351	5,500	7,000	8,500	58	2,222	14,180
6.4L V8 Hemi with MDS	8HP75 8 Speed	SRW	4.10	11,000	4,720	6,278	3,927	2,351	5,500	7,000	8,500	58	2,222	16,680
RAM 3500 4X4 CREWCAB TRADESMAN Box Delete Option [XBC]														
6.4L V8 Hemi with MDS	8HP75 8 Speed	SRW	3.73	11,400	5,020	6,377	4,050	2,326	5,500	7,000	8,500	58	2,123	14,010
6.4L V8 Hemi with MDS	8HP75 8 Speed	SRW	4.10	11,400	5,020	6,377	4,050	2,326	5,500	7,000	8,500	58	2,123	16,510

NOTES: Indicates Max Payload/Upfit Weight/Trailer Weight

Payload and Max Trailer Weights are ESTIMATED values
 All values are shown in pounds unless otherwise stated
 Payload and Max Trailer Weight values are rounded to the nearest 10 lbs
 Payload = GVWR - Base Weight
 GAWRs, GVWRs, and GCWRs should never be exceeded
 Recommended tongue weight determined by class hitch receiver and hardware limits of upfit
 Upfit or Aftermarket equipment weight not included in Base Weight
 MCVW: Maximum Completed Vehicle Weight, includes Total Base Weight + permanently attached Upfit Weight
 Frontal Area: Maximum allowable Frontal Area, in Ft², that the vehicle can project. For details on calculations please refer to Ram Body Builders Guide.